

**T系列内涨式
管子坡口机
T SERIES PIPEBEVELING
MACHINE**

Watt



T3

产品描述

整机采用“T”字形的结构设计，径向空间小，重量轻，便于携带，使用安全可靠。

专利号：ZL200320127316.4
ZL200530005895.X
ZL200430081901.5


FEATURES

The machine adopts “T” shape construction design, good rigidity, low weight, easy to operation and safe use.

Patent No.:ZL200320127316.4
ZL200530005895.X
ZL200430081901.5

标配刀具

STANDARD TOOLS



●如需加工其它角度坡口，或加工合金钢、铸钢，请订购前申明
Other bevel angles or alloy steel, cast steel, please declare before order

技术参数

电动式：碳刷电机驱动，电压110V或220V可选，频率：50~60Hz；
气动式：气动马达驱动，空气压力0.8~1.0Mpa，耗气量1500~3500L/min；

TECHNICAL PARAMETER

Electric: Driven by low-energy consumption electric motor 110V or 220V optional, 50-60Hz.
Pneumatic: Driven by pneumatic motor, Air working pressure: 0.8-1.0Mpa, Air Consuming flux:1500-3500L/min.

型号 Model	规格 size	加工范围 Capacity(LD mm)	坡口壁厚 Wall thickness(mm)	额定功率 Rated Power (kw)	刀头转速 Rotating speed (rpm)
电动T Electric: T	1-15	Φ12.5-15	≤3	1.43	3-70
	1-20	Φ15-20	≤5	1.43	3-70
	1-28	Φ20-28	≤6	1.43	3-70
气动QT Pneumatic: QT	3	Φ28-76	≤15	1.43	3-70
	4	Φ45-105	≤15	1.43	3-70
	6	Φ60-170	≤20	1.43	3-70
	12	Φ150-330	≤20	1.43	3-70
	24	Φ300-600	≤20	1.43	3-70



T6



T12

金属陶瓷刀具/cermet tools

